



Please note the following points for an optimal result of your printing:

max. printing area (W x D x H): 710 x 510 x 152 mm bzw. 2500 x 1300 x 50 mm

Scale: 1:1

minimum line thickness: min. 0,15 mm

Colours:

- Set up colours in CMYK format (also called Euroscale or 4C)
- **Printing in white is possible** and must be set in CMYK mode as follows: 0/0/1/0%
- Spot colours need to be clearly named as HKS K, RAL, Pantone C
Remark: Spot colours can only be printed approximately. They are mixed from the CMYK cartridges and therefore are not as color-consistent as the industrially mixed spot colours used in silkscreen printing.
- Colour gradients or shades are possible
- Please note: colours appear to look differently when used on light surfaces compared to dark surfaces
- Please note: the appearance of colours may vary between monitor and printing result if a non-calibrated monitor is used!
- in depressions up to approx. 2 mm can be printed under certain conditions, from 3 mm depth the print image becomes blurred.

File formats:

a) Vector graphics

- Formats: **CorelDraw (preferential), PDF, EPS (for PC), AI**
- all fonts in your artworks and in logos need to be converted to **paths**
- Please note: we can not make any changes on your texts

- Logos have to be sent separately:

- The logos have to be **Vector files** (Formats: **CorelDraw (bevorzugt), PDF, EPS (für PC), AI**)
You can get those files from your printer's shop, design agency or your marketing department.
- Vectorized logos in dxf or dwg may be used, but need to be checked first (case-by-case review)
- The following formats cannot be used:
 - Pixel files like JPEG, TIF, GIF, PNG, BMP (even if they are inserted into or included in vector files)
 - EPS, PDF or similar files that originate from a photo software
 - Word, PowerPoint or Excel files including the logo

Remark: simply changing or renaming the file format will not make the file useable as a vector file!

b) Pixel files

- PDF / JPG / TIFF / PNG / BMP with a resolution of min. 300 dpi
- Please note: pure white is left out, so that the colour of the underground shines through. The brightest printable white must be applied in CMYK mode as follows: 0/0/1/0%
- Pixel files are printed exactly as delivered. Changes to those files cannot be made by us.

**You have questions concerning digital printing or silkscreen printing?
Just ask us – we will be pleased to advise you!**